HP Latex R2000 Printer series



Sharpen the quality of any rigid substrate with the most vibrant colors, and glossiest white.



Achieve amazing colors on both rigid and flexible

- Get vibrant HP Latex color gamut on rigid while preserving media gloss and feel, and prints with no smell.³
- One technology for the same look across rigid and flexible campaigns lets you say goodbye to print and mount.
- Durable and flexible water-based ink for high adhesion and scratch resistance with a new HP Latex Overcoat.⁴

Expand your offering with the glossiest white²

- Glossiest white on transparent and colored media with high-opacity white that resists yellowing over time.²
- No waste between white jobs^s with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- Automatic maintenance makes white like any other color, including automatic recirculation and nozzle checks.

Increase your productivity with smarter printing

- Meet production peaks with a high-accuracy belt-driven system for continuous loading workflow.
- Advanced engineering drives high productivity with automatic maintenance, smart vacuum, and assisted loading.
- Maximize uptime with this smart printer for proactive and preventive services.

For more information, please visit http://www.hp.com/go/LatexR2000
Join the community, find tools, and talk to experts.
Visit the HP Latex Knowledge Center at http://www.hp.com/communities/LKC

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Most vibrant colors based on internal HP testing, January 2018 compared to leading competitive printers under \$350,000 USD. Tested in High Quality print mode on rigid (white acrylic 12-pass, 6-color, 120%). Internal HP testing with HP GamutViewer, Alpha Shapes=50000.

Clossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underflood samples. White ink capability may be optional, requiring purchase of the HP White Ink Option Kit.

³ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

⁴ HP Latex Overcoat improves scratch resistance on low-cost prints where lamination may be impractical or too expensive. Scratch resistance based on internal HP testing in January, 2018 demonstrating equivalent scratch-resistance performance for prints produced with HP Latex R Printer series and HP Latex Inks for the HP Latex 1500 Printer that provide scratch resistance comparable to representative hard-solvent inks on self-adhesive vinyl and PVC banner. Estimates by HP Image Permanence Lab on a range of media.

Lab on a range or media.

5 When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use

Technical specifications

Print	
Printing modes	20 m²/hr - Indoor High Quality (12p 120%) 46 m²/hr - Indoor Production (6p 110%) 88 m²/hr - Outdoor (3p 70%) 17 m²/hr - White Overflood (100%) 35 m²/hr - White Spot (100%) 17 m²/hr - Indoor High Quality (12p 120%) 520 ft²/hr - Indoor Hogh Quality (12p 120%) 520 ft²/hr - Outdoor (3p 70%) 1014 ft²/hr - Outdoor (3p 70%) 143 ft²/hr - White Spot (100%) 431 ft²/hr - White Spot (100%)
Ink types	HP Latex Inks
Ink cartridges	9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, HP Latex Overcoat, white)
Cartridge size	5 L (colors, HP Latex Optimizer, HP Latex Overcoat); 3 L (white)
Printheads	8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimizer, 2 white)
Long-term print-to-print repeatability	Average ≤ 1.0 dE2000, 95% of colors ≤ 2 dE2000 ²
Media	
Rigid media size	297×420 mm to 2489 \times 1220 mm (up to 2489 \times 3050 mm with two sets of optional extension tables); (11. \times 16.5 in to 98 \times 48 in (up to 98 \times 120 in with two sets of optional extension tables))
Thickness	Up to 50.8 mm (Up to 2 in)
Applications	Exhibition and event graphics; Exterior signage; Interior decoration; POP/POS; Short-run packaging; Textile; Vehicle graphics
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (w x d x h)	
Printer	$5.10\times2.04\times1.75$ m (printer); $5.10\times3.64\times1.75$ m (including standard input and output tables)
Shipping	5.32 x 2.24 x 2.15 m
Operating area	8.7 x 7.23 x 3 m (28.5 x 23.7 x 9.8 ft)
Weight	
Environmental ranges	
Operating temperature	15 to 30°C
Operating humidity	20 to 70% RH (non-condensing)
Power	
Consumption	10 to 12 kW (typical)
Certification	
Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD and MD compliant, EN60950-1, EN12100-1, ENIS013849-1, EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM)
Electromagnetic	$ Compliant \ with \ Class \ A \ requirements, including: \ USA \ (FCC \ rules), \ Canada \ (ICES), \ EU \ (EMC \ Directive), \ Australia \ (ACMA), \ New \ Zealand \ (RSM) $
Environmental	WEEE; RoHS (EU, China, Korea, Singapore, Turkey, Ukraine); India Waste Management Rules; REACH; CA 65 Prop; ErP Ecodesign Directive
Warranty	180-day limited hardware warranty. Warranty may vary by country as required by law. Go to http://www.hp.com/support to learn about HP service and support options in your region.

Ordering information

K0Q46A	HP Latex R2000 Plus Printer
Accessor	ies
T7V23A	HP Latex R2000 Extension Tables
Y6V16A	HP Latex R Series Edge Holders Rigid Kit
G0Z00A	HP 886 Latex Printhead Cleaning Kit
Original	HP printheads
G0Z21A	HP 886 White Latex Printhead
G0Z22A	HP 886 Optimizer Latex Printhead
G0Z24A	HP 886 Latex Printhead
Original	HP ink cartridges
G0Z10A	HP 882 5-liter Cyan Latex Ink Cartridge
G0Z09A	HP 886 3-liter White Latex Ink Cartridge
G0Z11A	HP 882 5-liter Magenta Latex Ink Cartridge
G0Z12A	HP 882 5-liter Yellow Latex Ink Cartridge
G0Z13A	HP 882 5-liter Black Latex Ink Cartridge
G0Z14A	HP 882 5-liter Light Cyan Latex Ink Cartridge
G0Z15A	HP 882 5-liter Light Magenta Latex Ink Cartridge
G0Z16A	HP 882 5-liter Optimizer Latex Ink Cartridge
G0Z17A	HP 882 5-liter Overcoat Latex Ink Cartridge
Original	HP large format printing materials
	n Removable Gloss Adhesive Vinyl
UD Dorman	ont Class Adhasiya Vinyl

HP Permanent Gloss Adhesive Vinyl HP Durable Backlit Fabric HP Everyday Blockout Display Film

Service and support

4BS24A/K0Q45-67270 HP Latex R Series Cleaning Kit 2WM39A/K0Q45-67267 HP Latex R Series Uptime Kit 2WM40A/K0Q45-67269 HP Latex R Series Expert Kit 2WP87A/K0045-67268 HP Latex R Series Reseller Kit K0Q45-67272 K0Q45-67273 HP Latex R Series Service Maintenance Kit HP Latex R Series White Service Maintenance Kit GOZOOA/KOQ45-60840 HP Latex Printhead Cleaning Kit

Eco Highlights

- Better for print operations—no hazard warning labels or HAPs, no localized ventilation needed1
- Better for the end-customer, more differentiation—odorless prints² go where solvent, UV
- Better for the environment—HP designs end-to-end sustainability into large-format
- $\bullet~$ HP Latex Inks—UL ECOLOGO $^{\circ}$ /UL GREENGUARD GOLD Certified 3 and ECO PASSPORT certified 4

Please recycle large-format printing hardware and printing supplies. Find out how at our website

hp.com/ecosolutions

¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Localized ventilation equipment (air Follitation is not required to meet U.S. OSHA requirements. Localized ventilation equipment elegibleria, us at the discretion of the customer—See the Site Preparation Guide for details. Customers should consult state adscretion of the customer—See the Site Preparation Guide for details. Customers should consult state adscretion.

 2 There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

performance of the final print.

3 UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see http://www.ul.com/EL). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to ULS GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.greenguard.org.

4 Original PI PLatex Inks for the PU Latex PR inter series are certified ECO PASSPORT by Oeko-Tex,** which is a globally uniform testing and certification system for textile chemicals, colorants, and auxiliaries. It consists of a two-step verification procedure that analyzes whether the compounds and each ingredient meet specific criteria for sustainability, safety, and regulatory compliance.









¹ Reflective measurements on a 943 color target under CIE standard illuminant D50, retriective measurements of a 434 color larget under CLE statioard munima and according to the standard ClEDE2000 as per ClE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.

² Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices, or can be returned through the HP Large Format Media take-back program. Recycling programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.